

AERUS

Protecting Indoor Air and Surfaces™



Features ActivePure Technology proven to reduce viruses, bacteria, and other pathogens (full list of tested pathogens available below in “The Proof”)

THE TECHNOLOGY

The Beyond by Aerus Guardian Heater combines ActivePure Technology with a ceramic heater, offering you both a heating and indoor space purifying option for the colder months. Patented ActivePure Technology is an advanced surface and air purification technology. It has been proven to reduce over 99.9% of many common airborne and surface contaminants (list of tested pathogens can be found in “The Proof” section below).

ActivePure Technology does not replace the need to follow public health guidelines and should be used as complementary technology.

THE PROOF

In extensive unaffiliated lab testing, ActivePure® Technology has been proven to significantly reduce the following contaminants and pathogens¹:

- SARS-CoV-2
- Staphylococcus Aureus
- Aspergillus niger endospores
- H1N1 Influenza
- H5N8 Influenza
- MRSA
- Bacillus globigii
- MS2 Bacteriophage
- Staphylococcus epidermidis
- PhiX-174
- Erwinia Herbicola
- Listeria monocytogenes
- Murine Norovirus
- E. coli
- Candida auris
- Botrytis cinerea
- Sclerotinia sclerotiorum
- Legionella pneumophila
- Aspergillus versicolor
- Clostridium difficile
- Salmonella enterica

THE BENEFITS

The Beyond by Aerus Guardian Heater provides 24/7 surface decontamination and air purification. It is a proactive and effective solution for your home or business.

- Portable, lightweight device
- No installation – plug-and-play solution
- Easy to use and low maintenance
- Proven effective against many common viruses, bacteria, molds, and fungi¹
- Reduces smoke, allergens, odors, and VOC gases without the use of ozone
- Option to run ActivePure Technology without heat for year-round protection



¹View test results at
Aeronline.com/Scientific-Proof

Inducted into the
2017 Space Technology
Hall of Fame by
the Space Foundation

BEYOND[®]

GUARDIAN HEATER

SPECIFICATIONS

Product Information	00689 Model: H181A NOTE: This unit does not meet California requirements and cannot be shipped to California.
Technology Included	ActivePure [®] Technology
Electrical	Input Voltage: 120 VAC 60 Hz Power Consumption: 500 Watts to 1,500 Watts
Mechanical	Heat Output: up to 5,100 BTU
Safety	Conforms to UL 1278
Weight & Dimensions	23 lbs (10.4 kg) 16.75" H x 13.125" W x 16.5" D (42.5 cm x 33.3 cm x 42 cm)
Coverage¹	Up to 1,000 sq. ft. (92.9 m ²) depending on occupant density and other factors. ¹ High density commercial not to exceed 1,000 sq. ft. (92.9 m ²).
Warranty	Limited 3 year warranty



Contact Name: _____



Email: _____



Phone Number: _____

1. Assumes 8 foot ceilings. Solutions should be customized based upon a variety of factors including HVAC system capabilities and settings, air flows taking into account walls, air pressure, and doors, ambient air temperatures and humidities, variable density, known VOC concentrations, and other layers of protection